

Physical Data

Length	Width	Height	Weight	
92 inches	51 inches	56 inches	1868	Pounds
234 cm	130 cm	142 cm	848	Kilogram

Engine Specifications

Mfg.	Bald or GE	Model	Industrial
Fuel	Electric	Engine Oil	NA
Volts	208 / 240 / 480	Rated Engine RPM	3600
Phase	single or three	Rated Engine Output	10 Hp
HZ	50 or 60		7.5 kW

Production Capability Data

*Rec. Minimum Tire Capacity	16.5" Car Tire Wheels
Ram/Punch Cycle Time	7 Seconds
Average Rim Weight	20 Pounds
	9.1 Kilograms
Average Hourly Production	160 Car Tires
Average Hourly Production based on Rim Weight	1800 Pounds
	816 Kilograms

*Rec = Recommended Size or Equivalent Size

Design and specifications are subject to change without notice

Hydraulic System Operating Parameters

Hydraulic Oil Tank Capacity	20 Gallons	Hydraulic Oil Specification	Dextron III High Temperature ATF
	75.7 Litres		
Hydraulic System Operating Pressure (Pressure @ Punch Cylinder)	2500 PSI		
	17,237 kPa		

Standard Product Features

Tire Loading Device	Adjustable Rim Sizer	Two-Stage Hydraulic Gear Pump	Operator Leg Shield
Operator Safety Shields	Hydraulic Pressure Gauge	Panel Box w/ Push-Button Start	Hydraulic Clamp & Ram
Greaseless Duralon Guide Roller Bushings		2nd Generation Ram/Clamp Assembly	Oil Tank Shut-Off
Floor Mounting Pads	3-point Lifting Padeyes	Heavy-Duty Steel Construction	Emergency Stop Button

Recommended Spare Parts List

Description	Qty	Part #	Description	Qty	Part #
Hydraulic Filter Element	2	10702	Valve Handle Clevis	2	10202
Valve Handle Kit	2	10200			

REUSE
 REDUCE
 RECYCLE



Eagle International, LLC, 389 W. Steamboat Drive, Dakota Dunes, South Dakota, USA 57049
 Toll Free (800) 755-8473 / Fax (605) 242-5217
 Email: tirecut@longlines.com / Website: www.eagle-equipment.com

