

Physical Data (Punch Arm Down)

Length	Width	Height	Weight	
273 inches	103 inches	122 inches	15500	pounds
694 cm	262 cm	310 cm	7031	kilograms

Working position = 366" long / 165" high / Tongue 4,000 lbs

Engine Specifications

Mfg.	Isuzu	Model	3CE1
Fuel	Diesel	Engine Oil	SAE 10W30
Volts	NA	Rated Engine RPM	2400
Phase	NA	Rated Engine Output	35 HP
HZ	NA		25.75 kW

Production Capability Data

Tire size range for bale production	Min = 13" car tire
	Max = 45" truck tire
Compaction Cycle Time	30 seconds
Average Weight of Tire Bale	2000 pounds/plus
	907 kilograms
Average Hourly Production	3 - 4 Tire Bales
Avg Hrly Production based on Tire Wgt	8000 pounds
	3628 kilograms

Design and specifications are subject to change without notice

Hydraulic System Operating Parameters

Hydraulic Oil Tank Capacity	70 gallons	Hydraulic Oil Specification	Dexron III Temperature ATF
	265 litres		
Hydraulic System Operating Pressure (Pressure @ Punch Cylinder)	2150 PSI		
	14,824 kPa		

Standard Product Features

Manual Tire loading	6 X 54 Compression Cylinders	Operator Safety Gate	5-Wire Bale Chamber
HD Platen Assembly	HD Steel Hold-Down Fingers	Operator Platform	6.5 Gallon Fuel Tank
70 Gallon Hydraulic Tank	Automated Door Lock	E-Stops on both sides	Oil & Temp Warning Lights
Hydraulic Door Locks	Hydraulic Override Limit Switch	Bale Ejector Chains	

Recommended Spare Parts List

Description	Qty	Part #	Description	Qty	Part #
Air Filter - Diesel	2	6603	Hydraulic Filter	2	6804
Oil Filter - Diesel	2	6601	Hold Down Finger	5	6099
Fuel Filter - Diesel	2	6602	Hold Down Spring	10	6100
Replacement Key - Diesel	1	6618			

REUSE

REDUCE

RECYCLE

