

Physical Data

Length	Width	Height	Weight
151 inches	67.37 inches	62.125 inches	1435 Pounds
157 cm	160.9 cm	383 cm	650 Kilograms

Engine Specifications

Mfg.	Kubota	Model	Z602
Fuel	Diesel	Engine Oil	SAE 10W30
Volts	12	Rated Engine RPM	3600
Phase	N/A	Rated Engine Output	14 Hp
HZ	N/A		10.43 kW

Production Capability Data

*Rec. Maximum Tire Capacity	44" O.D. Truck Tires
Average Cutting Time	10 Seconds
Average Hourly Production	100 Car Tires 70 Truck Tires
Average Hourly Production based on Rim Weight	500 Pounds 226 Kilograms

*Rec = Recommended Size or Equivalent Size

Design and specifications are subject to change without notice

Hydraulic System Operating Parameters

Hydraulic Oil Tank Capacity	20 Gallons	Hydraulic Oil Specification	Dexron III High Temperature ATF
	75.7 Litres		
Hydraulic System Operating Pressure (Pressure @ Punch Cylinder)	2500 PSI		
	17,237 kPa		

Standard Product Features

Tire Loading Device	Hydraulic Pressure Gauge	Hydraulic Gear Pump
Operator Safety Shields	Oil Tank Shut-Off	
8.5" Harden Cutting Blades	Hydraulic Gear Pump	
Heavy-Duty Steel Construction	Emergency Stop Button	

Recommended Spare Parts List

Description	Qty	Part #	Description	Qty	Part #
Hydraulic Filter Element	2	40054	Fuel Filter	1	40302
Valve Handle & Link Kit	1	40109	Replacement Key (Z602)	1	40303
Cutter Blade (8.5")	2	40029	Cutter Roller Pin Weldment	1	40505
Air Filter	1	40300	Cutter Roller w/Bushing	1	40142
Oil Filter	1	40301	Steel Roller Bushing	2	40143

REUSE
 REDUCE
 RECYCLE



Eagle International, LLC, 389 W. Steamboat Drive, Dakota Dunes, South Dakota, USA 57049

Toll Free (800) 755-8473 / Fax (605) 242-5217

Email: tirecut@longlines.com / Website: www.eagle-equipment.com

