

### Physical Data

Height	Width	Length	Weight	
64 inches	76 Inches	171 Inches	1850	Pounds
162.5 cm	193 cm	434 cm	833	Kilograms

With Treadcutting Attachment. Shipping width 75"

### Engine Specifications

Mfg.	Kohler	Model	CH20S
Fuel	Gas	Engine Oil	SAE10W30
Volts	12 Volt	Rated Engine RPM	3200
Phase		Rated Engine Output	20HP
HZ			14.9 kW

### Production Capability Data

*Rec. Maximum Tire Capacity	44" O.D. Truck Tires
Average Cutting Time	10 Seconds
Average Hourly Production	100 Car Tires
	70 Truck Tires
Average Hourly Production based on Rim Weight	500 Pounds
	226 Kilograms

\*Rec = Recommended Size or Equivalent Size

Design and specifications are subject to change without notice

### Hydraulic System Operating Parameters

Hydraulic Oil Tank Capacity	20 Gallons	Hydraulic Oil Specification	Dexron III High Temperature ATF
	75.7 Litres		
Hydraulic System Operating Pressure (Pressure @ Punch Cylinder)	2500 PSI		
	17,237 kPa		

### Standard Product Features

Tire Loading Device	Hydraulic Pressure Gauge	Hydraulic Gear Pump
Operator Safety Shields	Oil Tank Shut-Off	Emergency Stop Button
8.5" Harden Cutting Blades	Cutter Roller	Heavy-Duty Steel Construction

### Recommended Spare Parts List

Description	Qty	Part #	Description	Qty	Part #
Air Filter (Gas) 20HP	1	80051	Hydraulic Filter	2	80044
Pre-Clean Air Filter (Gas) 20HP	1	80052	Cutter Roller / Bushing Assembly	1	80142
Oil Filter (Gas) 20HP	1	80053	Cutter Roller Pin	1	80299
Fuel Filter (Gas) 20HP	1	80054	Cutter Blade (8.5")	2	80029
Replacement Key (Gas) 20HP	1	80055	Steel Bushing / Cutter Roller	2	80260

REUSE  
 REDUCE  
 RECYCLE

