

Physical Data (Punch Arm Down)

Length	Width	Height	Weight	
147 inches	84 inches	103 inches	4600	Pounds
373 cm	213 cm	261 cm	2086	Kilograms

Engine Specifications

Mfg.	GE / Balder	Model	
Fuel	N/A	Engine Oil	N/A
Volts	208/230/460/480	Rated Engine RPM	1800
Phase	3 Phase	Rated Engine Output	15 Hp
HZ	50 / 60		11.18 kW

Production Capability Data

Rec. Maximum Tire Capacity	19.5*25 GRADER TIRE ON DOWN
Ram Cycle Time / Punch	20 Seconds
Average Rim Weight	60 Pounds 27 Kilograms
Average Hourly Production	30 - 50 Tires / Rims
Avg Hrly Production based on Tire Wgt	1600 Pounds 725 Kilograms

*Rec = Recommended Size or Equivalent Size

Design and specifications are subject to change without notice

Hydraulic System Operating Parameters

Hydraulic Oil Tank Capacity	30 Gallons 113 Litres	Hydraulic Oil Specification	Dexron III High Temperature ATF
Hydraulic System Operating Pressure (Pressure @ Punch Cylinder)	2700 PSI 18,062.00 kPA		

Standard Product Features

Manual Tire Loading	Passenger Tire Plate	Piston Pump	Operator Leg Shield
Operator Safety Shields	Hydraulic Tilt Mechanism	Electric Brakes	Hydraulic Clamp & Ram
Greaseless Duralon Guide Roller Bushings		LT 235/85R16 Tires	Top Wind Jack
Emergency Stop Button	2" Hitch	Trailer Light Package	

Recommended Spare Parts List

Description	Qty	Part #	Description	Qty	Part #
Hydraulic Filter Element	2	20000			

REUSE
 REDUCE
 RECYCLE

