

Physical Data (Punch Arm Down)

Length	Width	Height	Weight	
87.5 Inches	83.5 Inches	76 Inches	3800	Pounds
222 cm	213 cm	194 cm	1723	Kilograms

Engine Specifications

Mfg.	GE / BALDER	Model	
Fuel	NA	Engine Oil	NA
Volts	208/230/460/480	Rated Engine RPM	1800
Phase	3 PH	Rated Engine Output	15 HP
HZ	50 / 60		11.18 kW

Production Capability Data

Rec. Maximum Tire Capacity	19.5*25 GRADER TIRE ON DOWN
Ram Cycle Time / Punch	20 Seconds
Average Rim Weight	60 Pounds
	27 Kilograms
Average Hourly Production	30 - 50 Tires / Rims
Avg Hrly Production based on Tire Wgt	1600 Pounds
	725 Kilograms

*Rec = Recommended Size or Equivalent Size

Design and specifications are subject to change without notice

Hydraulic System Operating Parameters

Hydraulic Oil Tank Capacity	30 Gallons	Hydraulic Oil Specification	Dexron III High Temperature ATF
	113 Litres		
Hydraulic System Operating Pressure (Pressure @ Punch Cylinder)	2700 PSI		
	18,062.00 kPA		

Standard Product Features

Manual Tire Loading	Emergency Stop Button	Piston Pump	Operator Leg Shield
Operator Safety Shields	Hydraulic Pressure Gauge	Panel Box w/ Push-Button Start	Hydraulic Clamp & Ram
Greaseless Duralon Guide Roller Bushings		2nd Generation Ram/Clamp Assembly	Oil Tank Shut-Off
Floor Mounting Pads	3-point Lifting Padeyes	Heavy-Duty Steel Construction	
Passenger Tire Plate			

Recommended Spare Parts List

Description	Qty	Part #	Description	Qty	Part #
Hydraulic Filter Element	2	20000			

REUSE
 REDUCE
 RECYCLE

