

### Physical Data (Punch Arm Down)

Length	Width	Height	Weight	
87.5 Inches	83.5 Inches	76 Inches	3800	Pounds
222 cm	213 cm	194 cm	1723	Kilograms

### Engine Specifications

Mfg.	Kohler	Model	CH20S
Fuel	Gas	Engine Oil	N/A
Volts	N/A	Rated Engine RPM	3200
Phase	N/A	Rated Engine Output	20 HP
HZ	N/A		14.91 kW

### Production Capability Data

Rec. Maximum Tire Capacity	19.5*25 GRADER TIRE ON DOWN
Ram Cycle Time / Punch	20 Seconds
Average Rim Weight	60 Pounds
	27 Kilograms
Average Hourly Production	30 - 50 Tires / Rims
Avg Hrlly Production based on Tire Wgt	1600 Pounds
	725 Kilograms

\*Rec = Recommended Size or Equivalent Size

Design and specifications are subject to change without notice

### Hydraulic System Operating Parameters

Hydraulic Oil Tank Capacity	30 Gallons	Hydraulic Oil Specification	Dexron III High Temperature ATF
	113 Litres		
Hydraulic System Operating Pressure (Pressure @ Punch Cylinder)	2700 PSI		
	18,062.00 kPA		

### Standard Product Features

Manual Tire Loading	Passenger Tire Plate	Piston Pump	Operator Leg Shield
Operator Safety Shields	Hydraulic Pressure Gauge	Oil Tank Shut-Off	Hydraulic Clamp & Ram
*Greaseless* Duralon Guide Roller Bushings		2nd Generation Ram/Clamp Assembly	Emergency Stop Button
Floor Mounting Pads	3-point Lifting Padeyes	Heavy-Duty Steel Construction	

### Recommended Spare Parts List

Description	Qty	Part #	Description	Qty	Part #
Hydraulic Filter Element	2	20000	Air Pre-Cleaner	2	20812
Ignition Switch & Key	1	20813	Oil Filter	2	20009
Air Filter	2	20811	Fuel Filter	2	20810

REUSE  
 REDUCE  
 RECYCLE

